

Product range

STRUCTURAL BEARINGS



Guarantee of high quality for the construction industry




Due to the combined effects of permanent static loads (dead load), live dynamic loads (e.g. wind) and concentrated restraints (e.g. due to temperature changes, creep, tolerances or settlements) relative movement within structures must always be considered. Without appropriate elastomeric bearings these influences will lead to damages. Beside cracks and spalling in concrete members, extensive deterioration can occur within adjacent structural members. The repair of those damages has significant time & cost implications.



Structural bearings concentrate high loads towards to the centre and can accommodate movements and rotations (angle of distortion) at the same time. Due to their low coefficient of friction, our sliding bearings are able to compensate large deformations and movements.

| UNREINFORCED BEARINGS | | | | | |
|---|-------------------------------|--|----------------|--|---|
| | Bearing name | Bearing type | Thickness [mm] | Compressive stress | Approval |
|  | Compact Bearing S 65 | Unreinforced deformation bearing | 5* | $\sigma_{R,d} = 14 \text{ N/mm}^2$ | Approval No. Z-16.32-474, issued by DIBt Berlin |
| | | | 8* | | |
| | | | 10 | | |
| | | | 15 | | |
| | | | 20 | | |
| | | | 25 | | |
|  | Compact Bearing S 70 | Unreinforced deformation bearing | 5* | $\sigma_{R,d} = 21 \text{ N/mm}^2$ | Approval No. Z-16.32-477, issued by DIBt Berlin |
| | | | 8* | | |
| | | | 10 | | |
| | | | 15 | | |
| | | | 20 | | |
|  | Compact Bearing CR 2000 | Unreinforced profiled deformation bearing | 11 | $\sigma_{R,d} = 28 \text{ N/mm}^2$ | Approval No. Z-16.32-435, issued by DIBt Berlin |
| | | | 16 | | |
| | | | 21 | | |
|  | bi-Trapez Bearing® | Unreinforced deformation for impact sound insulation | 5* | Shape depending (max. $\sigma_{R,d} = 17.4 \text{ N/mm}^2$) | Approval No. Z-16.32-455, issued by DIBt Berlin |
| | | | 10 | | |
| | | | 15 | | |
| | | | 20 | | |
|  | Cigular® Slab Bearing | Deformation bearing with low shear resistance | 10 | $\sigma_{R,d} = 1.5 \text{ N/mm}^2$ | Approval No. Z-16.32-479, issued by DIBt Berlin |
|  | Cigular® Slab Bearing EcoLine | Deformation bearing with low shear resistance | 10 | $\sigma_{R,d} = 1.5 \text{ N/mm}^2$ | Approval No. Z-16.32-479, issued by DIBt Berlin |

* without official approval

| REINFORCED BEARINGS | | | | | |
|---|-----------------------------|-------------------------------------|----------------|---|---|
| | Bearing name | Bearing type | Thickness [mm] | Compressive stress | Approval |
|  | Perforated™ Bearing, Type Z | Steel-reinforced perforated bearing | 15 | max. $\sigma_{R,d} = 35 \text{ N/mm}^2$ | Approval No. Z-16.33-481, issued by DIBt Berlin |
| | | | 24 | | |
| | | | 33 | | |
| | | | 42 | | |
| | | | 51 | | |
|  | Sandwich Bearing Q | Steel-reinforced bearing | 10 | max. $\sigma_{R,d} = 28 \text{ N/mm}^2$ | Approval No. Z-16.33-480, issued by DIBt Berlin |
| | | | 20 | | |
| | | | 30 | | |
| | | | 40 | | |

| SLIDING BEARINGS | | | | | |
|---|-------------------------------------|----------------------------------|----------------|---|--|
| | Bearing name | Bearing type | Thickness [mm] | Compressive stress | Approval |
|  | Type GFK Ciparall® Sliding Bearing | Reinforced point sliding bearing | 14 | Type GFK max. $\sigma_{R,d} = 21 \text{ N/mm}^2$ | Type GFK Approval No. Z-16.22-525, issued by DIBt Berlin |
| | Type ST Ciparall® Sliding Bearing | | 11 | Type ST max. $\sigma_K = 15 \text{ N/mm}^2$ | |
| | | | 20 | | |
| | | | 30 | | |
| | | | 40 | | |
|  | Perforated™ Sliding Bearing, Type Z | Reinforced point sliding bearing | 15 | max. $\sigma_K = 25 \text{ N/mm}^2$ | Approval applied According to DIBt official test certificate valid till approval issued |
| | | | 25 | | |
| | | | 34 | | |
| | | | 42 | | |
| | | | 51 | | |
|  | Civalit® Sliding Bearing | Point / strip sliding bearing | 11 | max. $\sigma_K = 15 \text{ N/mm}^2$ | Approval applied According to DIBt official test certificate valid till approval issued |

| SPECIAL PRODUCTS | | | | | |
|---|--------------------------|--|----------------|-------------------------------------|------------------|
| | Bearing name | Bearing type | Thickness [mm] | Compressive stress | Approval |
|  | Compact Core Bearing | Unreinforced heavy-duty bearing for thermal separation of steel structures | 5 | max. $\sigma_K = 30 \text{ N/mm}^2$ | Approval applied |
| | | | 10 | | |
| | | | 15 | | |
| | | | 20 | | |
|  | Cipolon® Edge Protection | Edge protection, sealing | 7 | Unnecessary | Unnecessary |



Am Knübel 2 - 4
31020 Salzhemmendorf | Germany

Tel. + 49 51 53 - 94 00-0
Fax + 49 51 53 - 94 00-49

info@calenberg-ingenieure.de
www.calenberg-ingenieure.com

A LISEGA Group Company

25 August 2023 | 8. edition | ©Calenberg Ingenieure GmbH | Subject to change



The contents of the publication in the result of many years of research an experience gained in application technology. All information is given in good faith; it does not represent a guarantee with respect to characteristics an does not exempt the user from testing the suitability of products and from ascertaining that the industrial property rights of third parties are not violated. No liability whatsoever will be accepted for damage – regardless of its nature and its legal basis – arising from advice given in this publication. This does not apply in the event that we or our legal representatives or our management are found guilty of having acted with intent or gross negligence. The exclusion of liability applies also to the personal liability of or legal representatives and employed in performing our obligations.